



BOILER INFORMATION:

Manufacturer Babcock & Wilcox

2000 Year

Superheated Steam Type

Capacity 75.000 PPH

750 PSI / 750°F Pressure

Burner Coen 670 FYR-Compac

CONNECTION SIZES:

8" 600# Flanged Main Steam

6" 150# Flanged Natural Gas

1-1/2" NPT #2. Oil

2-1/2" 600# Flanged Feedwater

1-1/2" 600# Flanged Bottom Blowdown

Continuous Blowdown



FUEL CONSUMPTION

121,400 SCFH Natural Gas

#2 Oil

827 GPH

CONTROLS:

Fireye ED 510 module / ED580 cable

ELECTRICAL POWER REQUIREMENTS:

480V, 3Ph, 60Hz, 200A

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

EMISSIONS DATA:

.12# / mmBtu w/ 18% FGR NOx

036# / mmBtu SO2.

CO .15# / mmBtu

PM

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height 38' / 10'-11" / 14'

Shipping Weight 107,000 lbs 134,000 lbs Operating Weight

ADDITIONAL INFORMATION

RB-747

O type watertube SH steam boiler. ASME Section I shell. Fuel valves & controls meeting FM, IRI, & NFPA8501 standards. Comes complete with gas train, (less regulator), oil train, No. 2 fuel oil pump, 1st & 2nd LWCO, pressure controls, flame safeguard, relief valves, feedwater and blowdown valves, one main steam stop valve, one stub stack section (6' tall), economizer, & FGR ductwork.