

800-228-8861 502-968-2211 rental.sales@wareinc.com www.wareinc.com

CTOCK EQUIPMENT

WARE Offers New/Used Equipment In Stock

BOILER INFORMATION

Manufacturer	York Shipley	
Year	2014	
Туре	Saturated Steam	
Capacity	175 HP / 6,037 PPH	
Pressure	150 PSI	
Burner	Powerflame C5-GO-30	

FUEL CONSUMPTION

Natural Gas	7,323 SCFH		
#2 Oil	52 GPH		
(C)	0	$' \Box \Box \Box \Box$	
ELECTRIC	AL POWER RE	QUIREMEN	TSP
480V, 3 F	Ph, 60 Hz	-	
		12-	
		1. 夜天村	下了
			作酒
		1	

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

CONNECTION SIZES

Main Steam	4" NPT
Natural Gas	2-1/2" NPT
#2 Oil	1" NPT
Feedwater	1-1/4" NPT
Bottom Blowdown	1-1/2" NPT
Continuous Blowdown	1-1/2" NPT

CONTROLS

Honeywell 7800 Series

EMISSIONS DATA

NOx .2# / mmBtu SO2 0# / mmBtu CO .15 #/mmBtu PM

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height202" / 75-3/8" / 85"Shipping Weight12,090 lbsOperating Weight20,750 lbs



ADDITIONAL INFORMATION

SB-213 Model: 560-SPH-175X-S150

Firetube Boiler, 3-Pass, Dryback, 175 BHP, 150 psig with a Powerflame Natural Gas & #2 Oil burner system. Burner has a 6:1 turndown ratio and is rated for 7.3 mmBtu gas input.

Package meets UL & CSD-1 codes.