



800-228-8861
 502-968-2211
 rental.sales@wareinc.com
 www.wareinc.com

STOCK EQUIPMENT

WARE Offers New/Used Equipment In Stock

BOILER INFORMATION

Manufacturer York Shipley
 Year 2015
 Type Saturated Steam
 Capacity 250 HP / 8,625 PPH
 Pressure 150 PSI
 Burner Powerflame CM9A-GO-30

CONNECTION SIZES

Main Steam 4" NPT
 Natural Gas 3" NPT
 #2 Oil 1" NPT
 Feedwater 1-1/2" NPT
 Bottom Blowdown 1-1/2" NPT
 Continuous Blowdown 1-1/2" NPT

FUEL CONSUMPTION

Natural Gas 10,468 SCFH
 #2 Oil 74.5 GPH

ELECTRICAL POWER REQUIREMENTS

480V, 3 Ph, 60 Hz

CONTROLS

Honeywell 7800 Series

EMISSIONS DATA

NOx .036# / mmBtu w/17% FGR
 SO2 .001# / mmBtu
 CO .15# / mmBtu
 PM .008# / mmBtu

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height 212" / 88" / 94"
 Shipping Weight 16,660 lbs
 Operating Weight 24,880 lbs



ADDITIONAL INFORMATION

SB-216
 Model: 564C-S3D-250X-S150-N2-LN

Firetube Boiler, 3-Pass, Dryback,
 250 BHP, 150 psig with a Powerflame
 Low NOx Natural Gas & #2 Oil burner
 system. Burner has a 6:1 turndown ratio
 and is rated for 10.5 mmBtu gas input.

Package meets UL & CSD-1 codes.

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.