

800-228-8861 502-968-2211 rental.sales@wareinc.com www.wareinc.com

WARE Offers New/Used Equipment In Stock

BOILER INFORMATION

Manufacturer	Victory Energy	
Year	2016	
Туре	Saturated Steam	
Capacity	70 HP / 2,415 PPH	
Pressure	150 PSI	
Burner	Powerflame C3-GO-20	

FUEL CONSUMPTION

Natural G	s 2,940 SCFH	-11
#2 Oil	21 GPH	Ц
		Î
ELECTR	CAL POWER REQUIREMENTS	う で 石
STR &	Ph, 60 Hz	-
The for		

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

CONNECTION SIZES

Main Steam	2-1/2" NPT
Natural Gas	1-1/2" NPT
#2 Oil	1" NPT
Feedwater	1" NPT
Bottom Blowdown	1-1/4" NPT
Continuous Blowdown	1-1/2" NPT

CONTROLS

Honeywell 7800 Series

EMISSIONS DATA

NOx .2# / mmBtu
SO2 0# / mmBtu
CO .15# / mmBtu
PM .008# / mmBtu

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height171" / 68" / 75"Shipping Weight6,500 lbsOperating Weight10,482 lbs



ADDITIONAL INFORMATION

SB-237 Model: F3-DB-548C-70-S150-SB

Firetube Boiler, 3-Pass, Dryback, 70 BHP, 150 psig with a Powerflame Natural Gas & #2 Oil burner system. Burner has a 6:1 turndown ratio and is rated for 2.94 mmBtu gas input.

Package meets UL & CSD-1 codes.