



BOILER INFORMATION:

Manufacturer Victory Energy

Year 2016

Type Saturated Steam

Capacity 70 HP / 2,415 PPH

Pressure 150 PSI

Burner Powerflame LNIC3-GO-20

CONNECTION SIZES:

Main Steam 2-1/2" NPT

Natural Gas 1-1/2" NPT

#2 Oil 1" NPT

Feedwater 1" NPT

Bottom Blowdown 1-1/4" NPT

Continuous Blowdown 1-1/2" NPT

FUEL CONSUMPTION

Natural Gas 2,940 SCFH

#2 Oil 21 GPH

CONTROLS:

Honeywell 7800 Series

ELECTRICAL POWER REQUIREMENTS

480V, 3 Ph, 60 Hz

EMISSIONS DATA

NOx .036# / mmBtu w/17% FGR

SO2 0# / mmBtu

co .15# / mmBtu

PM .008# / mmBtu

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height 171" / 68" / 75"

Shipping Weight 6,900 lbs

Operating Weight 10,882 lbs



ADDITIONAL INFORMATION

SSB-35

Model: F3-DB-548C-70-S150-SB-FGR

Firetube Boiler, 3-Pass, Dryback, 70 BHP, 150 psig with a Powerflame Low NOx Natural Gas & #2 Oil burner system. Burner has a 6:1 turndown ratio and is rated for 2.94 mmBtu gas input.

Package meets UL & CSD-1 codes.

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.