

800-228-8861 502-968-2211 rental.sales@wareinc.com www.wareinc.com

CTOCK EQUIPMENT WARE Offers New/Used Equipment In Stock

BOILER INFORMATION

Manufacturer	Victory Energy	
Year	2016	
Туре	Saturated Steam	
Capacity	150 HP / 5,175 PPH	
Pressure	150 PSI	
Burner	Powerflame LNIC5-GO-30	

FUEL CONSUMPTION

Natural G	as 6,300 SCFI	H	
#2 Oil	45 GPH		
	2-0	r	
FIFCTD	ICAL POWER R		TC.
F 31 8 1	3 Ph, 60 Hz		
100 v,		Je-	
		for the f	
A Carter			A

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

CONNECTION SIZES

Main Steam	4" NPT
Natural Gas	2-1/2" NPT
#2 Oil	3/8" NPT
Feedwater	1-1/4" NPT
Bottom Blowdown	1-1/2" NPT
Continuous Blowdown	1-1/2" NPT

CONTROLS.

Honeywell 7800 Series

EMISSIONS DATA

- NOx .036# / mmBtu w/17% FGR
- so2 .001# / mmBtu
- ^{CO} .15 # / mmBtu
- PM .008# / mmBtu

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height212" / 77" / 90"Shipping Weight12,090 lbsOperating Weight20,611 lbs



ADDITIONAL INFORMATION

SSB-38 Model: F3-DB-560C-150-S150-SB-FGR.

Firetube Boiler, 3-Pass, Dryback, 150 BHP, 150 psig with a Low NOx Powerflame Natural Gas & #2 Oil burner system. Burner has a 6:1 turndown ratio and is rated for 6.3 mmBtu gas input.

Package meets UL & CSD-1 codes.